


Gotham[®]

Porcelain Stone[®]

Colors



AV321 ▶ Lamp Post



AV322 ▶ Penthouse



AV323 ▶ Clock Tower



AV324 ▶ Mainline



AV325 ▶ Dockside



AV326 ▶ Pavement

Features and Benefits

- Subtle striations and aggregate finishes create a depth and integrity
- Each tile color in the Gotham series takes inspiration and its name from iconic cityscapes.
- Sizes offered 12 x 24 and 2 x 6
- Trim includes 4 x 24 single bullnose and 6 x 12 covebase (universal flat-top)
- Cross-Sheen[®] finish for easy cleaning
- Green SquaredSM certified and Made in the USA
- Plank shapes are also available through Crossville's Get Planked[®] program, which offers a variety of plank sizes with no minimum order and a short lead time



Gotham[®]

Porcelain Stone[®]

Sizes Available in all colors

2 x 6

12 x 24



Sizes & Finishes

Field Tile

Available in all colors

| Nominal (in) | Actual (in) | Thickness (in) | Grout Joint (in) | Finish |
|--------------|---------------------|----------------|------------------|--------|
| 2 x 6 | 1-13/16 x 5-13/16 | 3/8 | 3/16 | UPS |
| 12 x 24 | 11-13/16 x 23-13/16 | 3/8 | 3/16 | UPS |

All field tile is calibrated (non-rectified).
Crossville recommends a minimum 3/16" grout joint.


Coordinating Trim

Available in all colors

| Nominal (in) | Actual (in) | Thickness (in) | Grout Joint (in) | Finish |
|------------------------|--------------------|----------------|------------------|--------|
| 4 x 24 Single Bullnose | 3-13/16 x 23-13/16 | 3/8 | 3/16 | UPS |
| 6 x 12 Cove Base | 5-7/8 x 11-3/4 | 3/8 | 3/16 | UPS |



4 x 24 Single Bullnose



6 x 12 Cove Base
(universal flat top)

Product Performance

| | | |
|---------------------|------------|------------|
| Breaking Strength | >450 lbf | ASTM C648 |
| Bond Strength | >200 psi | ASTM C482 |
| Chemical Resistance | Unaffected | ASTM C650 |
| Frost Resistance | Resistant | ASTM C1026 |
| Water Absorption | <0.20% | ASTM C373 |
| Scratch Hardness | 7 | Mohs Scale |

Wet Dynamic Coefficient of Friction Range

| | | |
|-----|-----------|-----------------------|
| UPS | .50 – .60 | AcuTest SM |
|-----|-----------|-----------------------|

Shade & Texture Index

Gotham[®] has a shade variation of V2.

| | | | | | | | | |
|----|--|----|--|----|--|----|--|----------------------------|
| V1 | | V2 | | V3 | | V4 | | V1 Uniform appearance |
| | | | | | | | | V2 Slight Variation |
| | | | | | | | | V3 Moderate Variation |
| | | | | | | | | V4 Substantial Variation |

This porcelain tile product is produced with a V2 variation. Expect that the amount of color and texture on each piece may vary slightly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

Get Planked!

Our Porcelain Stone[®] products are available in popular plank shapes with no minimum order and quick fulfillment.

See website for more details and sizes.



AV325 ▶ Dockside 12 x 24



Crossville, Inc. PO Box 1168
Crossville, TN
38557

Phone 931.484.2110
Fax 931.456.2956
E-Mail Crossc@CrossvilleInc.com
Web CrossvilleInc.com

Recommended Use

Gotham® is recommended for interior floors, walls, countertops, and exterior walls in both residential and commercial applications. Gotham is not recommended for exterior horizontal surfaces or exterior paving. **If offset pattern is required for tiles 15 inches or longer, Crossville® recommends an offset of not greater than 33%.** See CrossvilleInc.com for detailed installation instructions

Care and Maintenance

Regular cleaning is the best way to keep Gotham® tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.



AV323 ▶ Clock Tower 12 x 24
L4338 ▶ Laminam by Crossville 5.6
Fokos - Piombo

Green SquaredSM Certified

Crossville® has earned Green SquaredSM certification from the Tile Council of North America (TCNA) for its entire U.S.-manufactured porcelain product line-up, as well as its manufacturing processes. The company is among the first ever recipients of this certification standard for the tile industry. TCNA developed the Green Squared certification under American National Standards Institute (ANSI) process. The multi-attribute program (ANSI A138.1) scores products in five categories of performance: product characteristics, manufacturing, corporate governance, innovation and end-of-life. Crossville's certified products and processes received stringent evaluation from Scientific Certification Systems (SCS), the green building industry's longest standing third-party certifier.

Hydrotect

Our porcelain tiles are available with Hydrotect™. Crossville's revolutionary invisible coating harnesses the power of light, water, and oxygen to create the best defense against dirt and pollution. Whether indoors or out, floors and walls stay cleaner, providing a superior experience in any space. Please request a sample before ordering. For complete details check our website at CrossvilleInc.com.



▶▶ Crossville® Sample Express

Visit the website to learn more:
CrossvilleInc.com/Products/Gotham

Loose Samples for
Architects & Designers

Loose Tile Samples
Sizes may vary depending on product series
Max. of 4 large field tile per order

Replacement Chips for PSS Rack
Max. of 5, 2 x 2 chips per color

Standard Shipping
UPS Ground

National Accounts

For over 20 years we have been offering Porcelain tile to commercial customers at National Accounts pricing programs with special discounts. The National Accounts department provides materials forecasting, sales support and samples.

Exterior Cladding

Crossville's Porcelain Stone® Exterior Cladding Systems are suitable for virtually any conventional masonry application. When used in conjunction with our exterior cladding systems, Crossville's Porcelain Stone offers clear advantages: decreased construction costs, less site disturbance, low-to-zero maintenance after installation, accelerated construction schedules and greater strength than traditional masonry.

Our Warranty

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1-2012 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.

Trade Organizations



Environmentally Aware

