

WALNUT

This stunning collection has the rich look and wide color range of exotic Brazilian hardwood; replicated in an extremely durable, high-definition porcelain tile.









ANA62-734 WALNUT

ANA62-733

| Available Sizes | Thickness 9mm ≭ | |
|-----------------|-----------------|--|
| | | |
| | | |
| 8 x 48* | | |
| | | |
| 6 x 36 | 6 x 24 | |

* 10mm thickness

BLEND

| Technical Specifications | | | |
|--------------------------|--|-----------|----------------|
| Product Performance | Tile | Result | Testing Method |
| Water Absorption | All | ≤ 0.5% | ISO 10545-3 |
| Breaking Strength | All | ≥ 300 lbf | ISO 10545-4 |
| Frost Resistance | All | Resistant | ISO 10545-12 |
| Chemical Resistance | All | Class A | ISO 10545-13 |
| Abrasion Resistance | All | 4 PEI | ISO 10545-7 |
| Scratch Hardness | All | 7 | MOHS |
| DCOF Wet | All | ≥ 0.50 | ANSI B101.3 |
| Shade Variation | All | V4 | |
| Grout Thickness | All | 3/16" | |
| Usage | Amaya is suitable for interior floors and interior and exterior walls in both residential and commercial applications. | | |